

## BLE AoA Gateway and Beacon for Enterprise-grade RTLS Solutions



AiRISTA's Angle of Arrival Gateway applies the latest Bluetooth® Low Energy (BLE) technology in a compact design to provide location insights of people and assets to under 1 meter of accuracy.

A series of micro antennas precisely located on the substrate compare the "angle" of an incoming BLE signal. Minute differences in the arriving angles are traced back to a point of intersection which represents the location of the signal source. Location is also tracked in the vertical dimension, providing x,y,z coordinates.

Unlike other designs, a single AiRISTA Angle of Arrival Gateway can provide submeter accuracy (configuration dependent). AiRISTA's proprietary echo cancelation techniques overcome what had been one of the final hurdles to making location accuracy with less than one (1) meter using a single BLE angle of arrival reader that produces industry leading performance.

### Applications

Combined with low cost BLE tags, retailers can automate inventory accounting. Warehouses can provide guided picking instructions including vertical shelves. Hospitals can track and automatically assign equipment relative to the patient's body. Manufacturing routing applications ensure accurate paths of vehicles. Industrial tools can be programed based on position.

- Workflows & alerts
- Analytics & reports
- Low-code dev. env.
- Route monitoring
- People/patient flow
- Staff safety

BLE is proving to do more at lower costs.

### Unified Vision Solution Support

AiRISTA's Unified Vision Solution software platform (UVS) creates the business value from location insights provided by the gateway.

### Benefits

- Submeter location accuracy using standards-based technology
- Support for most existing AiRISTA BLE tags
- Location provided in the vertical dimension (x,y,z coordinates)
- Submeter accuracy from a single device eliminating the need for 3 or more gateways (configuration dependent)
- Integration with popular third-party access points (vendor dependent)

### Features

- Ethernet, Wi-Fi and USB connectivity
- Power derived from PoE or USB
- Adjustable angle of view
- Mountable at any angle for wider coverage

# Technical Specifications

## BLE Angle of Arrival Gateway Submeter Accuracy in a Compact Design

### Two BLE Radios

Power Consumption:  
RX BLE: 5 mA  
TX BLE at 0dBm: 6 mA  
Firmware configurable transmit power: -6dBm to +4dBm  
Operating Current TX & RX Disable: 10uA Cortex M3  
Maximum Output Power: +5dBm  
Default Output Power: 0dBm  
RX Sensitivity -94 dB

### PoE Ethernet Interface

Compatible with IEEE 802.3af  
Supports Static and Dynamic IP address  
Supports Backup Server IP Address List  
Over LAN configuration  
Built-in Http based management interface

### Wi-Fi Radios

Supported Wi-Fi Networks: 802.11 b/g/n  
FCC, Canada, ETSI 2.4 - 2.4835 GHz Japan 2.471 -2.497 GHz  
Layer 2 Network Support: CCX, Blink  
Security: WEP, WPA2-PSK  
Supported Data Rates, 1, 6,11,54,72 Mbps

### Electrical Interface

Certification: FCC and CE  
Current Consumption: 1A

### Antenna Specifications

Internal Antenna 1: internal Omni-directional  
Internal Antenna 2: AoA Antenna with 16 Micro antennas  
with 1-2 Micro Second RF Switching

### Environment

Operating Temperature: 32 to 122 °F / 0 to 55°C  
Storage Temperature: -40 to 140 °F / -40 to 60 °C  
\*outdoor installation requires NEMA 4X enclosures

### Typical Operating Range

Device in TX mode  
**Line of Sight:**  
BLE +4dBm 1MBps: ~150ft/50m  
**Obstructions:**  
BLE +4dBm 1MBps: ~75ft/25m

AoA Receiver range varies based on the installation height, angle of view and transmitting BLE device's TX output power settings. Please see AoA Reader Technical Configuration Guide for details.

### Physical

Dimensions:  
6.63 x 4.68 x 1.63 in / 168.40 x 118.87 x 41.40 mm.  
Weight: 0.64 Lbs

### Part Number

AoA Beaconsing Gateway: BGU.AoA

### Accessories

Swivel Wall Mount: PSU.MB

### Warranty

One Year Warranty

AiRISTA Flow, Americas  
913 Ridgebrook Rd. | Suite 110  
Sparks, MD | 21152 | USA  
Tel: 1-844-816-7127  
salesinfo@airista.com

AiRISTA Flow, APAC  
Level 9 Wyndham Building  
1 Corporate Court  
Gold Coast | QLD | Australia  
Tel: +61-7-3053-8375

AiRISTA Flow, EMEA  
Espoo | Finland  
salesinfo@airista.com